

## ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):	Pidra 14										
Indirect heating functionality:	yes										
Direct heat output:					13,1						
Indirect heat output:					10,9						
Fuel	Preferred fuel (only one):	Other suitable fuel(s):	η <sub>s</sub> [%]:	Space heating emissions at nominal heat output (*)				Space heating emissions at minimum heat output (*) (**)			
				PM	OGC	СО	NO <sub>x</sub>	PM	OGC	СО	NO <sub>x</sub>
				mg/Nm <sup>3</sup> (13%O <sub>2</sub> )			mg/Nm <sup>3</sup> (13%O <sub>2</sub> )				
Wood logs with moisture content ≤ 25 %	no	no									
Compressed wood with moisture content < 12 %	yes	no	84,7	14	2	23	83	23	10	173	90
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



## Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit		
Heat output					
Nominal heat output	P <sub>nom</sub>	13,1	kW		
Minimum heat output (indicative)	P <sub>min</sub>	5,1	kW		
Auxiliary elettricity consumption					
At nominal heat output	el <sub>max</sub>	0,050	kW		
At minimum heat output	el <sub>min</sub>	0,035	kW		
In standby mode	el <sub>SB</sub>	0,003	kW		
Permanent pilot flame power requirement					
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	n.p.	kW		

Item	Symbol	Value	Unit		
Useful efficiency (NCV	ed)				
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	95,4	%		
Useful efficiency at minimum heat output (indicative)	$\eta_{\text{th,min}}$	96,7	%		
Type of heat output/ro	om tempe	rature cont	rol (select		
one)					
single stage heat outputemperature control	no				
two or more manual room temperature control	yes				
with mechanic thermo	no				
with eletronic room to	no				
with eletronic room tempearture control plus day timer		no			
with eletronic room to control plus week timer	no				
Other control options (multiple selections possible)					
room temperature co presence detector	ntrol, with	no			
room temperature co open window detection	ntrol, with	no			

Contact details	Name and address of the manufacturer or its authorised representative
+39 0445 741310 +39 0445 741657	THERMOROSSI S.p.A.
export@thermorossi.it www.thermorossi.com	Via Grumulo, 4 - 36011 Arsiero (VI) - IT

with distance control option

(\*) PM = particulate matter,  $\overrightarrow{OGC}$  = organic gaseous compounds,  $\overrightarrow{CO}$  = carbon monoxide,  $\overrightarrow{NO}_x$  = nitrogen oxides

(\*\*) Only required if correction factors F(2) or F(3) are applied

Note:

F(2) 1 F(3) 0

Technical report ref. 2005504/01

Approved by

Maurizio Lorenzon

Industry Division Manager

porenton blaunte

Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO)
Tel. +39.051.459.3.111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it
P.I. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.