

## ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):			SI	_IMQU	ADRO	LUMI	A				
Indirect heating functionality:					no						
Direct heat output:					10,2						
Indirect heat output:					-						
Fuel	Preferred fuel (only	Other suitable	ղ <sub>s</sub> [%]։	emi:	Space ssions neat ou	at nom	ninal )	emis he	Space sions a at outp	at mini	mum **)
	one): fu	fuel(s):		PM	OGC	СО	NO <sub>x</sub>	PM	OGC		NO <sub>x</sub>
				mg/Nm <sup>3</sup>		m <sup>3</sup> (13%O <sub>2</sub> )		mg/Nm <sup>3</sup> (13%O <sub>2</sub> )			) <sub>2</sub> )
Wood logs with moisture content ≤ 25 %	no	no									
Compressed wood with moisture content < 12 %	yes	no	83	12	5	62	94	16	18	331	102
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



## Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit		
Heat output					
Nominal heat output	P <sub>nom</sub>	10,2	kW		
Minimum heat output (indicative)	$P_{min}$	2,8	kW		
Auxiliary elettricity consumption					
At nominal heat output	el <sub>max</sub>	0,088	kW		
At minimum heat output	el <sub>min</sub>	0,067	kW		
In standby mode	el <sub>SB</sub>	0,004	kW		
Permanent pilot flame power requirement					
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	n.p.	kW		

Item	Symbol	Value	Unit		
Useful efficiency (NCV as received)					
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	94,4	%		
Useful efficiency at minimum heat output (indicative)	$\eta_{\text{th,min}}$	96,4	%		
Type of heat output/ro one)	om tempe	rature cont	rol (select		
single stage heat output temperature control	it, no room	no			
two or more manual room temperature control	no				
with mechanic thermotemperature control	no				
with eletronic room to control	no				
with eletronic room to control plus day timer	no				
with eletronic room to control plus week timer	no				
Other control options (multiple selections possible)					
room temperature co	ntrol, with	no			

with

no

no

room temperature control,

open window detection
with distance control option

Contact details	Name and address of the manufacturer or its authorised representative
+39 0445 741310 +39 0445 741657	THERMOROSSI S.p.A.
info@thermorossi.it www.thermorossi.com	Via Grumulo, 4 - 36011 Arsiero (VI) - IT

(\*) PM = particulate matter,  $\overrightarrow{OGC}$  = organic gaseous compounds,  $\overrightarrow{CO}$  = carbon monoxide,  $\overrightarrow{NO}_x$  = nitrogen oxides (\*\*) Only required if correction factors F(2) or F(3) are applied

Note:

F(2) 0 F(3) 0

Technical report ref. 2011400

Approved by

Maurizio Lorenzon

Mustry Division

Anager