

## ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):				С	HICCA	\					
Indirect heating functionality:					no						
Direct heat output:					7,2						
Indirect heat output:					-						
Fuel	Preferred fuel (only	Other suitable	ղ <sub>s</sub> [%]։	emi	Space ssions neat ou	at non	ninal )	emis he	sions a	heating at minin out (*) (	mum **)
	one): f	fuel(s):		PM	OGC g/Nm <sup>3</sup>		NOx	PM	OGC	(13%C	NO <sup>x</sup>
Wood logs with moisture content ≤ 25 %	no	no		III	g/NIII	(13%0	) <sub>2</sub> )	1119	g/INIII	(13%C	) <sub>2</sub> )
Compressed wood with moisture content < 12 %	yes	no	80	14	1	95	98	28	2	158	118
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



## Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit	
Heat output				
Nominal heat output	P <sub>nom</sub>	7,2	kW	
Minimum heat output (indicative)	P <sub>min</sub>	2,1	kW	
Auxiliary elettricity consumption***				
At nominal heat output	el <sub>max</sub>	0,088	kW	
At minimum heat output	el <sub>min</sub>	0,067	kW	
In standby mode	el <sub>SB</sub>	0,004	kW	
Permanent pilot flame power requirement				
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	n.p.	kW	
	·	·		

Item	Symbol	Value	Unit	
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	91,6	%	
Useful efficiency at minimum heat output (indicative)	$\eta_{\text{th,min}}$	91,4	%	
Type of heat output/room temperature control (select				
one)		•		
single stage heat outputemperature control	no			
two or more manual stroom temperature control	no			
with mechanic thermotemperature control	no			

## Other control options (multiple selections possible)

nο

no

no

	temperature ce detector	control,	with	no	
	temperature vindow detecti		with	no	
with distance control option no					

with eletronic room tempearture

with eletronic room tempearture

with eletronic room tempearture

control plus day timer

control plus week timer

control

Contact details	Name and address of the manufacturer or its authorised representative		
+39 0445 741310	THEDMODOCCI C n A		
+39 0445 741657	THERMOROSSI S.p.A.		
export@thermorossi.it	Via Grumulo, 4 - 36011 Arsiero (VI) - IT		
www.thermorossi.com	Via Gruffiulo, 4 - 30011 Afsiero (VI) - 11		

<sup>(\*)</sup> PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO<sub>x</sub> = nitrogen oxides

Note:

F(2) 0 F(3) 0

Technical report ref. 2011606

Approved by Maurizio Lorenzon Industry Division Manager

Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO)
Tel. +39.051.459.3,111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it
P.I. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.

<sup>(\*\*)</sup> Only required if correction factors F(2) or F(3) are applied

<sup>(\*\*\*)</sup> Declared by the manufacturer