

## ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):				PAI	R12EV	<b>/</b> 0					
Indirect heating functionality:					no						
Direct heat output:					12,1						
Indirect heat output:					-						
Fuel	Preferred fuel (only	Other suitable	ղ <sub>s</sub> [%]։	emi:	Space ssions neat ou	at nom	ninal )	emis he	Space sions a at outp	at mini	mum (**)
	one):	fuel(s):		PM	OGC		NO <sub>x</sub>	PM	OGC	СО	NO <sub>x</sub>
				m	mg/Nm <sup>3</sup> (13%O <sub>2</sub> )			mg/Nm <sup>3</sup> (13%O <sub>2</sub> )			
Wood logs with moisture content ≤ 25 %	no	no									
Compressed wood with moisture content < 12 %	yes	no	83	13	9	148	98	13	12	471	100
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



## Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit		
Heat output					
Nominal heat output	P <sub>nom</sub>	12,1	kW		
Minimum heat output (indicative)	P <sub>min</sub>	3,5	kW		
Auxiliary elettricity consumption					
At nominal heat output	el <sub>max</sub>	0,162	kW		
At minimum heat output	el <sub>min</sub>	0,018	kW		
In standby mode	el <sub>SB</sub>	0,003	kW		
Permanent pilot flame power requirement					
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	n.p.	kW		

Item	Symbol	Value	Unit	
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	93,8	%	
Useful efficiency at minimum heat output (indicative)		93,0	%	
Type of heat output/ro	om tempe	rature cont	rol (select	
one)		Ī	Ī	
single stage heat output	no			
temperature control	110			
two or more manual room temperature control	no			
with mechanic thermo				
temperature control	no			
with eletronic room tempearture control		no		
with eletronic room tempearture control plus day timer		no		
with eletronic room to control plus week timer	no			
Other control options	(multiple s	elections p	ossible)	

					$\overline{}$
room	temperature	control,	with	no	
presence detector				110	
room	temperature	control,	with	no	
open v	110				
with distance control option no					

Contact details	Name and address of the manufacturer or its authorised representative			
+39 0445 741310 +39 0445 741657	THERMOROSSI S.p.A.			
export@thermorossi.it www.thermorossi.com	Via Grumulo, 4 - 36011 Arsiero (VI) - IT			

(\*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO<sub>x</sub> = nitrogen oxides

(\*\*) Only required if correction factors F(2) or F(3) are applied

Note:

F(2) 0 F(3) 0

Technical report ref. 3003277

> Approved by **Maurizio Lorenzon** Industry Division Manager

> > llaurotz

Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO)
Tel. +39.051.459.3.111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it
Pl. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.